and commercial applications.



PRODUCT TYPE: Glazed porcelain

COLOURS: Warm White, Almond Beige, Grey and

Charcoal

SIZES:

60x200mm, 300x300mm, 300x600mm,

600x600mm and 600x1200mm

Rectified Edges

FINISHES/USAGE: Matt and Grip/Wall and Floor

AESTHETIC QUALITIES: Mix stone surface

ORIGIN: N/A

TECHNICAL DATA: P3 Pendulum Slip rating (Matt)

P5 Pendulum Slip rating (Grip)

P5 Pendulum Slip rating (Grip Paver) More technical data on last page

CERTIFICATIONS:







PRODUCT INFORMATION



Warm White

 Matt
 60x200mm | 300x300mm | 300x600mm

 600x600mm | 600x1200mm

 Grip
 300x600mm | 600x600mm

 Grip Paver
 600x600x20mm



Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.



Almond Beige

 Matt
 60x200mm | 300x300mm | 300x600mm

 600x600mm

 Grip
 300x600mm | 600x600mm

 Grip Paver
 600x600x20mm



Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.



Grey

 Matt
 60x200mm | 300x300mm | 300x600mm

 600x600mm | 600x1200mm

 Grip
 300x600mm | 600x600mm

 Grip Paver
 600x600x20mm



Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.



Charcoal

 Matt
 60x200mm | 300x300mm | 300x600mm

 600x600mm

 Grip
 300x600mm | 600x600mm

 Grip Paver
 600x600x20mm



Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.

WARM WHITE VARIATION





- 600x1200mm 10 tile faces
- **600x600mm** 20 tile faces

ALMOND BEIGE VARIATION





- 600x1200mm 10 tile faces
- 600x600mm 20 tile faces

GREY VARIATION



- 600x1200mm 10 tile faces
- **600x600mm** 20 tile faces

CHARCOAL VARIATION



- 600x1200mm 10 tile faces
- 600x600mm 20 tile faces

TECHNICAL DATA - TILE

| | technical characteristics | test method | required values | result |
|--------------|---------------------------|--------------|-----------------|--------|
| δ δ δ δ δ | water absorption | ISO 10545-3 | ≤0.5% | ≤0.5% |
| 5 | breaking strength | ISO 10545-4 | ≥1300N | 2265N |
| £03 | shock resistance | ISO 10545-11 | Pass | Pass |
| | chemical resistance | ISO 10545-13 | Declared value | Pass |
| | resistance to frost | ISO 10545-12 | Resistant | Pass |
| | staining resistance | ISO 10545-14 | Minimum Class 3 | Pass |

TECHNICAL DATA - PAVER

| | technical characteristics | test method | result |
|--|---------------------------|--------------|--------|
| ۵ ۵ ۵ ۵ ۵ | water absorption | ISO 10545-3 | ≤0.5% |
| 50 | breaking strength | ISO 10545-4 | 8500N |
| E CONTRACTOR OF THE PARTY OF TH | max warpage | ISO 10545-2 | ±2.0mm |
| 5 | max edge curvature | ISO 10545-2 | ±2.0mm |
| | chemical resistance | ISO 10545-13 | Pass |
| | resistance to frost | ISO 10545-12 | Pass |
| | staining resistance | ISO 10545-14 | Pass |

Porcelain Pavers and Coping tiles must be installed to Australian Standards (AS 3958.1, AS 3958.2 & AS 3727-2016) using correct procedures and products such as Mapei Ultralite S1.

No spot fixing under any circumstances.

Please note that all products must be fabricated using score & snap method and/or wet cutting in conjunction with AS/NZS 1716:2012, AS/NZS 1715:2009, AS/NZS 60335.2.69:2017" For more information please refer to: https://www.safework.nsw.gov.au

CERTIFICATIONS



ISO 14001:2015 specifies the requirements for an environmental management system that an organization can use to enhance its environmental performance. ISO 14001:2015 is intended for use by an organization seeking to manage its environmental responsibilities in a systematic manner that contributes to the environmental pillar of sustainability.